

Technical Report No.: 350 - 0047 - 03- FBTK Ext. 1
Manufacturer: KTM Sportmotorcycle AG, Mattighofen (Austria)
Type of Vehicle: Husaberg FE01

2002/24/EC

Page 2

1 General

1.1 Make KTM Sportmotorcycle AG, Mattighofen
(Austria)

1.2 Typ / Type Husaberg FE01

1.2.1. Commercial description (variants/ versions):

Variants A: Husaberg 450 FE
Variants B: Husaberg 501 FE
Variants C: Husaberg 550 FE
Variants D: Husaberg 650 FE

Versions optionally for all variants:

a: 18" tyres on the rear wheel
b: 17" tyres on the rear wheel

Optional for all variants/ versions: lh: for left hand traffic
rh: for right hand traffic

1.3 Name and address of the
Manufacturer: KTM Sportmotorcycle AG
Stallhofner Str. 3
A-5230 Mattighofen

1.4 Name and address of the
manufacturer's representative: not applicable

Technical Report No.: 350 - 0047 - 03- FBTK Ext. 1
Manufacturer: KTM Sportmotorcycle AG, Mattighofen (Austria)
Type of Vehicle: Husaberg FE01

2002/24/EC

Page 7

6 Tyres

Version a

Tyres

Axle 1	90/90 - 21 54 M
with	
Axle 2	140/80 - 18 65 M
alternatively	
Axle 1	90/90 R 21 54 M
with	
Axle 2	140/80 R 18 65 M
or	
Axle 1	80/100 - 21 54 M
or	
Axle 2	120/80 - 18 65 M
or	
Axle 2	120/90 - 18 65 M

in the combinations:

- all Pirelli and Metzeler tyres with tread profiles C and D (according E.T.R.T.O)
- Bridgestone:
 - axle 1: ED 661 with axle 2: ED660
- Michelin:
 - axle 1: Enduro Competition III
 - e-mark: E2 75R-006570
 - axle 2: Enduro Competition III
 - e-mark: E2 75R-006501

only tyres from the same manufacturer can be combined

with rim from manufaktor D.I.D or Exel

axle 1: 1.60 x 21
axle 2: 2.15 x 18

Technical Report No.: 350 - 0047 - 03- FBTk Ext. 1
Manufacturer: KTM Sportmotorcycle AG, Mattighofen (Austria)
Type of Vehicle: Husaberg FE01

2002/24/EC

Page 8

Version b

	Tyres	Rim
Axle 1	120/70 - 17 54 M	3.50x17
with		
Axle 2	150/60 - 17 65 M	4.25x17 or 5x17
opt.		
Axle 2	160/60 - 17 65M	4.25x17 or 5x17
Alternatively		
Axle 1	120/70 R 17 54 M	3.50x17
with		
Axle 2	150/60 R 17 65 M	4.25x17 or 5x17
opt.		
Axle 2	160/60 R 17 65M	4.25x17 or 5x17

- only tyres with an ECE component type approval are permitted

- with rim from manufaktor D.I.D or Exel

axle 1: 3.50x17

axle 2: 4.25x17 or 5x17

7 Braking system

ER 93/14/EWG fulfilled
See attachment 5

8 Installation of lighting and light signal devices

ER 93/92/EWG attachment IV fulfilled